



## KENT KVT170 (RDSL) - Commercial Gully (High Footfall)

The KVT170 (SQSL) Gully is a Round Top stainless steel gully with Curved Slotted Grating for tiled and poured floor areas. It has a heavier duty top than our KVT162 and can take heavier traffic, but this top is primarily 'chunky' for aesthetic reasons. It is supplied as standard with a lockdown grating.

### Features

- Grade 304 (1.4301) or 316 (1.4401) Stainless Steel to BS EN 10088
- 110mm diameter outlet
- Satin finish as standard
- Customised perforated patterns available
- Lock down as standard



**Pedestrian**



**Barefoot**



**Forklift**

**BS EN1253 Loading Class K3 (L15 or R50 or M125 variations available)**

Product Code	Height	Width	Depth	Outlet	Flow Rate	Description
KVT170/110TP (RDSL)	105	170	170	110	1.4 l/s	Top Part Only Bottom Outlet 110mm
KVT170/110 (RDSL)	200-250	170	170	110	1.4 l/s	Adjustable Height 2 Part Bottom Outlet - See Page 4
KHT170/50(RDSL)	140-185	170	170	50	0.9 l/s	Adjustable Height 2 Part Side Outlet 50mm - See Page 4
KHT170/1.5"(RDSL)	140-185	170	170	1.5"	0.9 l/s	Adjustable Height 2 Part Side Outlet 1.5" - See Page 4
Trap						110mm Trap with 50mm water seal

**Specify Kent KVT170/110TP (RDSL) Floor Gully. 170mm diameter, fixed height floor drain. Grade 304 stainless steel with a satin polish finish, supplied with KFT110 Trap.**